

E-Z-GO GAS TXT

STANDARD EQUIPMENT:

Engine:	9.0 HP (6.7 KW) rated, 4 cycle, 18 ci (295 cc) twin cylinder, air cooled, by Robin USA.
Valve train:	Overhead valve, overhead cam with belt drive.
Lubrication:	Pressurised oil system, washable permanent filter.
Balancer:	Internal counter rotating balance shaft.
Ignition:	Solid state with crank trigger, electronic timing advance and RPM limiter.
Carburettor:	Fixed jet float bowl with remote pulse fuel pump.
Air Cleaner:	Engine mounted integral air intake system with multi-phase silencer and washable cartridge.
Electrical:	Starter/generator, solid state regulator, 12 volt maintenance free battery, 430 CCA, 60 minute reverse.
Drive Train:	Automatic, continuously variable transmission (CVT).
Transaxle:	High efficiency helical gears, 13.32:1 ratio, ground speed governor, forward/reverse with neutral lock.
Brakes:	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings. Automatic park brake release with self-compensating system.
Front Suspension:	Leaf springs with hydraulic shock absorbers.
Rear Suspension:	Leaf springs with hydraulic shock absorbers.
Steering:	Self-compensating single reduction rack and pinion.
Fuel System:	6 gallon (22.8 l) tank.
Speed:	Automatically governed to 12-14 MPH (19-23 KPH) on level ground.

DIMENSIONAL SPECIFICATIONS:

Weight:	668 lbs (304 KG) dry.
Length:	92.6 inches (2.35m)
Width:	46.5 inches (1.18m)
Height:	48.6 inches (1.23m) at steering wheel
Wheel Base:	65.5 inches (1.66m)
Front Wheel Tread:	33.5 inches (0.85m)
Rear Wheel Tread:	38.0 inches (0.97m)
Clearance Circle:	18.9 feet (5.72m)
Tires:	18 x 8.50 x 8 (4 ply rated)
Load Capacity:	800lbs (362 KG) including operator, passengers, accessories, and cargo.
Seating:	Vacuum formed fabric backed vinyl covers over thick cushion foam. Standard seating for operator and one passenger.

FEATURES:

Body & Finish:	Durashield™ body of automotive quality injection moulded TPE (thermoplastic elastomer). Molded-in colour with automotive colour coat/clear coat finish.
Chassis:	Welded high yield strength tubular steel with Durashield™ powder coat paint.
Safety:	Dash mounted key switch, reverse warning indicator, "deadman" accelerator control, integral handgrip on hip restraints, manual forward/reverse selector.
Dash Panel:	Tee, ball, and 4 position drink holders of scuff resistant glass fiber reinforced thermoplastic olefin.
Steering Wheel:	Hi-tech design with dual handgrips, pencil holder, integral scorecard holder.

Specifications subject to change without notice.